

SAFETY DATA SHEET



Date Issued : 03/06/2023
SDS No : Water Born Primer A-side

WB Primer and Sealer A-side

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WB Primer and Sealer A-side
GENERAL USE: Epoxy resin side of a 2 component product.
PRODUCT CODE: 153401

MANUFACTURER

Fiberglass Coatings Inc.
4301A 34th Street North
St. Petersburg, FL 33714
Customer Service: (800) 272-7890
E-Mail: www.fgci.com
Emergency Contact: VelocityEHS
Emergency Phone: (800) 255-3924

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Sensitization, Category 1

GHS LABEL



Exclamation
mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H320: Causes eye irritation.
H315: Causes skin irritation.
H335: May cause respiratory irritation.

PRECAUTIONARY STATEMENT(S)

General:

P202: Do not handle until all safety precautions have been read and understood.

Prevention:

P280: Wear protective gloves/protective clothing/eye protection/face protection.
P262: Do not get in eyes, on skin, or on clothing.
P270: Do not eat, drink or smoke when using this product.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P272: Contaminated work clothing should not be allowed out of the workplace.
P285: In case of inadequate ventilation wear respiratory protection.
P273: Avoid release to the environment.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P341: If inhaled: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call for medical assistance.

Storage:

P233+P235: Keep container tightly closed at a cool to ambient temperature.

Disposal:

P501: Dispose of contents/container to a RCRA approved Treatment Storage Disposal Facility.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Can cause eye, skin and respiratory tract irritation. Prolonged exposure may cause skin sensitization.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
DGEBA based Epoxy Resin	25 - 50	25068-38-6
Hydroxy-Carbomonocyclic- alkyl-carbomonocyclic-hydroxid, polymer with heteromonocyclic- alkyl- halogenide	2.5 - 5	T/S

COMMENTS: Alternative CAS numbers for the product known as DGEBA 25068-38-6, include 25085-99-8, and 1675-54-3.

Accordingly, Liquid Epoxy Resins (LER) manufacturers consider that derivatives of LERs may be described using either CAS number as a starting material.

Mixture; Other components below reportable levels.

4. FIRST AID MEASURES

EYES: Immediately Flush eyes with a large amount of water for at least 15 minutes, while holding eyelids open. Rest eyes for several minutes. If redness, burning, blurred vision or swelling persist, consult a physician.

SKIN: Remove contaminated clothing. Wash skin with soap and water. Obtain medical attention If irritation persists. Wash clothing before reuse.

INGESTION: Rinse mouth with water. Do not induce vomiting, seek medical attention if feeling unwell.

INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

NOTES TO PHYSICIAN: No specific treatment, treat symptomatically. Call medical doctor or a Poison Control center immediately if large quantities have been ingested or inhaled.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not categorized as Flammable by GHS standards.

EXTINGUISHING MEDIA: Use water spray, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

EXPLOSION HAZARDS: This product is not considered to be an explosion hazard.

FIRE FIGHTING PROCEDURES: Adjust firefighting measures to suit the surrounding environment. Cool exposed tanks/containers with water sprays.

FIRE FIGHTING EQUIPMENT: In confined spaces, Full Bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus (SCBA), may be necessary.

HAZARDOUS DECOMPOSITION PRODUCTS: Hazardous decomposition products may include but are not limited to Phenolics, Carbon Dioxide, and Carbon Monoxide.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in approved container for disposal according to Local, State and Federal regulations.

LARGE SPILL: Evacuate surrounding areas, keep unnecessary and unprotected individuals from the area. Dam off any possible routes to the environment or any waterways. Wear an appropriate respirator, avoid breathing vapors or mist. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or RCRA approved Waste Facility. Processing or contamination of this product may change the waste management options. State and Local disposal regulations may differ from Federal Disposal Regulations.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Prevent from entering into ditches, drains, sewers, waterways, and/or groundwater.

LAND SPILL: Prevent material from being absorbed into the soil, treat contaminated soil as hazardous waste.

GENERAL PROCEDURES: Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

COMMENTS: Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or RCRA approved Waste Facility

7. HANDLING AND STORAGE

HANDLING: Use proper protective equipment to prevent eye or skin contamination, use eye protection, gloves, and adequate clothing, and do not use around food or drink to avoid possible ingestion of the material. Avoid breathing mist or vapors and use only with adequate ventilation. Keep the material tightly closed in original container.

STORAGE: Components of this product may settle out and need to be stirred back into solution.

STORAGE TEMPERATURE: Storage is best at Room Temperatures and below to maintain product viability, but Do Not Allow the Product to Freeze.

ELECTROSTATIC ACCUMULATION HAZARD: None Expected.

COMMENTS: This product has a limited shelf life and should be stored cool.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide ventilation or other engineering controls to keep the airborne concentrations of vapors or mists below any applicable workplace exposure limits (PEL/TLV). An installed emergency eye wash station or safety showers should be located near the work area.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical splash goggles and/or face shield. Always use proper eye protection around the work area.

SKIN: Wear solvent resistant gloves (consult safety equipment supplier). To prevent repeated or prolonged skin contact, wear impervious clothing and boots.

RESPIRATORY: Wear appropriate respirator when ventilation is inadequate.

WORK HYGIENIC PRACTICES: Never eat or drink in areas where the chemical is being used. Wash hands after exposure.

COMMENTS: This material is typically used with an Amine type curing agent which may generate heat and significantly alter the precautions necessary for its safe usage.

If 2 or more components are combined for use, than all the associated Data Sheets involved must be read and understood,.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous liquid.

ODOR: Odorless to mild.

ODOR THRESHOLD:

COLOR: White.

pH: 6 to 8

FLASH POINT AND METHOD: > 251°C (483°F) PMCC ASTM D 93

FLAMMABLE LIMITS: Not Applicable.

AUTOIGNITION TEMPERATURE: Not Applicable.

VAPOR PRESSURE: Negligible.

VAPOR DENSITY: No test data available.

BOILING POINT: ~ 100°C (212°F)

FREEZING POINT: 0°C (32°F)

Notes: Do not allow the material to freeze.

SOLUBILITY IN WATER: Mostly Soluble

EVAPORATION RATE: No data available.

DENSITY: 9.68 pounds/ gallon

SPECIFIC GRAVITY: 1.1 to 1.2 (Water = 1) at 20°C (68°F)

(VOC): 0 %

10. STABILITY AND REACTIVITY

REACTIVITY: Stable under recommended storage conditions.

STABILITY: This product is stable and will not hazardously polymerize.

POSSIBILITY OF HAZARDOUS REACTIONS: A Hazardous Polymerization of this product will not occur by itself, however mixing this product with an amine type curing agent as it is intended to be used will cause an irreversible polymerization with considerable heat build up.

HAZARDOUS DECOMPOSITION PRODUCTS: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

INCOMPATIBLE MATERIALS: Avoid all unplanned contact with strong reactive chemicals, Acids, Bases, Amines, Epoxides, Peroxides and other Oxidizers.

COMMENTS: This material will not hazardously polymerize on its own, but may undergo a reversable crystallization.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

DERMAL LD₅₀: ~ 23000 mg/kg (Rat)

Notes: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

ORAL LD₅₀: ~ 15000 mg/Kg (Rat)

Notes: Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

NOTES: Values based on DGEBA CAS 25068-38-6

SKIN CORROSION/IRRITATION: Prolonged / repeated skin contact may cause skin irritation with local redness.

SERIOUS EYE DAMAGE/IRRITATION: May cause eye irritation. Corneal injury is unlikely. Vapour may cause eye irritation experienced as mild discomfort and redness.

RESPIRATORY OR SKIN SENSITIZATION: Dermal sensitization to this product or the chemical components of it have been seen in some humans. The results of a test on guinea pigs showed this substance to be a weak skin sensitizer. Sensitization has occurred in laboratory animals after repeated exposures.

CARCINOGENICITY

NOTES: Not considered carcinogenic by OSHA, NTP, IARC, or ACGIH

COMMENTS: Product has not been tested as a unique formulation, only the individual components have been tested and listed.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Moderately Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Not readily biodegradable. This product shows a moderate bioaccumulation potential. Water polluting material. May be harmful to the environment if released in large quantities.

ECOTOXICOLOGICAL INFORMATION: Do NOT discharge into sewers or waterways.

BIOACCUMULATION/ACCUMULATION: Not readily biodegradable. Moderate potential to bioaccumulate (LogPow in the range 2.6 to 3.8).

AQUATIC TOXICITY (ACUTE): Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations.

PRODUCT DISPOSAL: Incinerate or dispose of in a permitted disposal facility. Do not discharge substance/product into sewer system.

EMPTY CONTAINER: Empty containers must be disposed of in accordance with all Federal, State, and local requirements.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated by DOT

TECHNICAL NAME: Epoxy Resin

AIR (ICAO/IATA)

SHIPPING NAME: Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)

TECHNICAL NAME: Epoxy Resin

UN/NA NUMBER: 3082

PRIMARY HAZARD CLASS/DIVISION: 9

PACKING GROUP: III


VESSEL (IMO/IMDG)

SHIPPING NAME: Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)

TECHNICAL NAME: Epoxy Resin

UN/NA NUMBER: 3082**PRIMARY HAZARD CLASS/DIVISION:** 9**PACKING GROUP:** III**MARINE POLLUTANT #1:** Epoxy Resin**COMMENTS:** This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications and product segregation rules may vary by container volume and geographical region..**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HEALTH HAZARDS:** Acute Health Hazard, Chronic Health Hazard., Eye Irritation, Skin Irritation, Skin Sensitization**311/312 PHYSICAL HAZARDS:** No dangerous reaction known under conditions of normal use.**313 REPORTABLE INGREDIENTS:** The material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.**302/304 EMERGENCY PLANNING****EMERGENCY PLAN:** None required**TSCA (TOXIC SUBSTANCE CONTROL ACT)****TSCA REGULATORY:** All components are TSCA listed**CLEAN AIR ACT (HAZARDOUS AIR POLLUTANTS):** None present or none in regulated quantities**CALIFORNIA PROPOSITION 65:** No data available.**CLEAN WATER ACT:** None present or none in regulated quantities**CANADA****WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** Class D-2B: Toxic material causing other toxic effects.**DOMESTIC SUBSTANCE LIST (INVENTORY):** Listed.**16. OTHER INFORMATION****PREPARED BY:** RD **Date Prepared:** 03/06/2023**HMIS RATING**

HEALTH	*	1
FLAMMABILITY		1
PHYSICAL HAZARD		1
PERSONAL PROTECTION		

NFPA CODES**MANUFACTURER DISCLAIMER:** This information is compiled from sources believed reliable as of the date of issue, it is provided in good faith and correct to the best of our knowledge. No warranty, guarantee, or representation is made as to the sufficiency of the information for the safe use of the product nor to relieve the end user of their own Federal, State, and local regulatory compliance requirements.

SAFETY DATA SHEET



Date Issued : 03/06/2023
SDS No : Water Born Primer B-side

WB Primer and Sealer A-side

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: WB Primer and Sealer A-side
GENERAL USE: Activator side of a 2 component product.
PRODUCT CODE: 153401

MANUFACTURER

Fiberglass Coatings Inc.
4301A 34th Street North
St. Petersburg, FL 33714
Customer Service: (800) 272-7890
E-Mail: www.fgci.com
Emergency Contact: VelocityEHS
Emergency Phone: (800) 255-3924

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Irritation/Corrosion, Category 1B
Serious eye damage/eye irritation, Category 1
Skin Sensitization, Category 1

GHS LABEL



Corrosion



Exclamation
mark

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.

PRECAUTIONARY STATEMENT(S)

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P262: Do not get in eyes, on skin, or on clothing.
P202: Do not handle until all safety precautions have been read and understood.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P350: IF ON SKIN: Gently wash with plenty of soap and water.
P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P337+P313: If eye irritation persists: Get medical advice/attention.
P341: If inhaled: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call for

medical assistance.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501: Dispose of contents/container to an EPA approved TSD Facility

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
3-aminomethyl-3,5,5-trimethylcyclohexylamine	< 30	2855-13-2
Water	> 10	7732-18-5
Phenol, 4,4-(methylethylidene) bis polymer with 2-(chloromethyl)oxirane,(oxy-1,2-ethanediyl, an dpolyamine	< 50 - 60	T/S
Polyamine Polymer	< 5 - 10	T/S

COMMENTS: Mixture; Other components below reportable levels.

4. FIRST AID MEASURES

EYES: Flush eyes for at least 15 minutes, holding eyelids open. Do not use eye ointment. If easily accomplished, check for and remove contact lenses. If contact lenses cannot be removed, seek immediate medical attention.

SKIN: Flush with water, then wash with soap.

INGESTION: Aspiration hazard. If swallowed, Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration into lungs. Rinse mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.

INHALATION: Move to fresh air if symptoms develop. If breathing is difficult, give oxygen and call physician.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not categorized as Flammable by GHS standards.

GENERAL HAZARD: Remove all unprotected personnel. The burning decomposition products should be treated as potentially hazardous substances and appropriate precautions taken.

EXTINGUISHING MEDIA: Alcohol-resistance foam. Carbon dioxide (CO₂). Dry chemical. Dry sand. Limestone powder.

HAZARDOUS COMBUSTION PRODUCTS: May form: carbon dioxide and carbon monoxide, various hydrocarbons, and nitrogen oxides.

OTHER CONSIDERATIONS: Do not allow run-off from fire fighting to enter drains or water courses.

FIRE FIGHTING EQUIPMENT: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

FIRE EXPLOSION: Unlikely

COMMENTS: Causes skin and eye irritation and possible damage..

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

LARGE SPILL: Create a dike further ahead of the spill to control spill for large scale clean up.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

GENERAL PROCEDURES: Always ensure proper ventilation from any spill. Respirators or SCBA are required if permissible exposure limits are exceeded due to inadequate general ventilation. Evacuate personnel to a safe area. Contain spillage to avoid any soil or water contamination

COMMENTS: Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved incinerator or RCRA approved Waste Facility

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Avoid breathing and contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Use the information in this data sheet to assess risks in local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

HANDLING: Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not flush with water. Do not flush

into surface water. Water pollutant. Water runoff can cause environmental damage.

STORAGE: Store in a cool, dry, well-ventilated area. Keep container closed when not being used.

ELECTROSTATIC ACCUMULATION HAZARD: None Expected.

COMMENTS: Personal Protective Equipment for eye and skin exposure is required, see Section 8; for specific recommendations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical splash goggles. Always use proper eye protection around the work area.

SKIN: Avoid skin contact. Use heavy duty gloves made of Viton or heavy nitrile rubber. Wash hands with plenty of mild soap and water. Wear long-sleeved resistant clothing, remove and discard contaminated clothing immediately.

RESPIRATORY: In case of inadequate ventilation, a NIOSH approved respirator may be required if Occupational Exposure Limits are exceeded.

PROTECTIVE CLOTHING: Clothing should be applicable for the job at hand to protect the skin from repeated exposure to the material.

OTHER USE PRECAUTIONS: A safety shower and eye wash fountain should be readily available.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Viscous Colored Liquid.

ODOR: Amine Odor.

COLOR: Varying color.

PHYSICAL STATE COMMENTS: Syrup like.

pH: ~ 8 to 12.1

FLASH POINT AND METHOD: 102°C (212°F)

FLAMMABLE LIMITS: No data available.

VAPOR PRESSURE: 23.86 hPa

BOILING POINT: 100°C (212°F)

FREEZING POINT: 0°C (32°F)

Notes: Do not allow the material to freeze.

MELTING POINT: Not Applicable.

SOLUBILITY IN WATER: Soluble in water

EVAPORATION RATE: No data available.

SPECIFIC GRAVITY: ~ 1 to 1.06

10. STABILITY AND REACTIVITY

REACTIVITY: No

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions of use.

STABILITY: Stable under recommended storage conditions. Avoid contact with incompatible materials.

POSSIBILITY OF HAZARDOUS REACTIONS: Not yet Known

INCOMPATIBLE MATERIALS: Avoid all unplanned contact with strong reactive chemicals, Acids, Bases, Amines, Epoxides, Peroxides and other Oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

DERMAL LD₅₀: > 5000 mg/kg

Notes: Estimate

ORAL LD₅₀: No data available.

INHALATION LC₅₀: No data available.

SKIN CORROSION/IRRITATION: Prolonged / repeated skin contact may cause skin irritation with local redness.

SERIOUS EYE DAMAGE/IRRITATION: Causes skin and eye irritation and possible damage..

RESPIRATORY OR SKIN SENSITIZATION: No test data available.

GERM CELL MUTAGENICITY: No test data available.

CARCINOGENICITY

Chemical Name	NTP Status
Water	Not Listed.

REPRODUCTIVE TOXICITY: No data available.

ASPIRATION HAZARD: May be harmful if swallowed and enter airways.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No test data available.

BIOACCUMULATION/ACCUMULATION: Not yet determined.

AQUATIC TOXICITY (ACUTE): No data available.

COMMENTS: While the material has no known significant risks or critical hazards, good stewardship of the environment requires care to not release this material into the soil or water.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: All disposal practices must be in compliance with Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations.

EMPTY CONTAINER: Empty containers may contain product residue.

COMMENTS: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Amines, Liquid, Corrosive n.o.s. (3-Aminomethyl-3,5,5-trimethylcyclohexamine)

TECHNICAL NAME: Water Born Floor Primer Activator

PRIMARY HAZARD CLASS/DIVISION: 8

UN/NA NUMBER: 2735

PACKING GROUP: II

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Amines, Liquid, Corrosive n.o.s. (3-Aminomethyl-3,5,5-trimethylcyclohexamine)

UN NUMBER: 2735

HAZARD CLASS: 8

PACKING GROUP: II

VESSEL (IMO/IMDG)

SHIPPING NAME: Amines, Liquid, Corrosive n.o.s. (3-Aminomethyl-3,5,5-trimethylcyclohexamine)

UN/NA NUMBER: 2735

PRIMARY HAZARD CLASS/DIVISION: 8

PACKING GROUP: II

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HEALTH HAZARDS: Acute Health Hazard, Serious eye and skin damage possible., Respiratory Tract Irritation, Skin Sensitization

311/312 PHYSICAL HAZARDS: Not yet Known

313 REPORTABLE INGREDIENTS: None of the chemicals in this product are subject to the reporting requirements of Section 313

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: No CERCLA Reportable Quantity has been established for this product.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Water	7732-18-5

TSCA REGULATORY: All components are TSCA listed

CLEAN AIR ACT (HAZARDOUS AIR POLLUTANTS): None present or none in regulated quantities

OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None Present

CALIFORNIA PROPOSITION 65: Not Listed

CLEAN WATER ACT: None present or none in regulated quantities

16. OTHER INFORMATION

PREPARED BY: RD **Date Prepared:** 03/06/2023

HMIS RATING

HEALTH	<input type="text"/>	2
FLAMMABILITY	<input type="text"/>	0
PHYSICAL HAZARD	<input type="text"/>	0
PERSONAL PROTECTION	<input type="text"/>	

NFPA CODES

